Frame Fixing Screw

Frame fixing screw with TX star recess-drive and self-tapping thread.

| Code | Description | Anchor Ø | Length | Drill | Box Qty |
|------------|------------------------------|----------|--------|-------|---------|
| FFS7.5X42 | Window and door frame anchor | 7.5mm | 42mm | 6.5mm | 100 |
| FFS7.5X52 | Window and door frame anchor | 7.5mm | 52mm | 6.5mm | 100 |
| FFS7.5X62 | Window and door frame anchor | 7.5mm | 62mm | 6.5mm | 100 |
| FFS7.5X72 | Window and door frame anchor | 7.5mm | 72mm | 6.5mm | 100 |
| FFS7.5X82 | Window and door frame anchor | 7.5mm | 82mm | 6.5mm | 100 |
| FFS7.5X92 | Window and door frame anchor | 7.5mm | 92mm | 6.5mm | 100 |
| FFS7.5X102 | Window and door frame anchor | 7.5mm | 102mm | 6.5mm | 100 |
| FFS7.5X112 | Window and door frame anchor | 7.5mm | 112mm | 6.5mm | 100 |
| FFS7.5X122 | Window and door frame anchor | 7.5mm | 122mm | 6.5mm | 100 |
| FFS7.5X132 | Window and door frame anchor | 7.5mm | 132mm | 6.5mm | 100 |
| FFS7.5X152 | Window and door frame anchor | 7.5mm | 152mm | 6.5mm | 100 |
| FFS7.5X182 | Window and door frame anchor | 7.5mm | 182mm | 6.5mm | 100 |
| FFS7.5X202 | Window and door frame anchor | 7.5mm | 202mm | 6.5mm | 100 |
| FFS7.5X212 | Window and door frame anchor | 7.5mm | 212mm | 6.5mm | 100 |

Flat head for metal and plastic windows, cylindrical head for recessed installation with wooden windows.

Advantages/benefits

Stress-free stand-off installation without additional plugs.

Universal use for all common building and frame materials

Tapered thread diameter at the front for easy attachment. Optimised thread for a smooth, easy turn action.

Only a 6 mm drill diameter necessary, thereby reduced work.

The continuous thread prevents the fixture being pulled up against the building material. Cover caps to conceal fixing

For fixing of: Windows Door frames

Fire protection doors

Squared timbers











Pan head Tapcon anchors

| Code | Description | Anchor Ø | Length | Drill | Box Qty |
|------|-------------------|----------|--------|-------|---------|
| 4P30 | Pan tapcon anchor | 5.5mm | 30mm | 4mm | 250 |
| 4P40 | Pan tapcon anchor | 5.5mm | 40m | 4mm | 250 |
| 5P30 | Pan tapcon anchor | 6.5mm | 30mm | 5mm | 250 |
| 5P40 | Pan tapcon anchor | 6.5mm | 40mm | 5mm | 250 |



| Code | Description | Anchor Ø | Length | Drill | Box Qty |
|-----------|---------------------------------|----------|--------|-------|---------|
| 5WP32 | Washered Pan Head Tapcon Anchor | 6.5mm | 32mm | 5mm | 250 |
| | | | | | |
| | | | | | |
| Dome Head | I Tapcon Anchors T30 drive | | | | |
| Code | Description | Anchor Ø | Length | Drill | Box Qty |
| 6D35 | Dome Tapcon Anchors | | 35mm | 6mm | 100 |
| 6D45 | Dome Tapcon Anchors | | 45mm | 6mm | 100 |
| 6D60 | Dome Tapcon Anchors | | 60mm | 6mm | 100 |

| Code | Description | Anchor Ø | Length | Drill | Box Qty |
|-------|-----------------------------|----------|--------|-------|---------|
| 16648 | M8 x 35mm Tapcon Rod Hanger | 7.5mm | 35mm | 6mm | 50 |
| 16649 | M10x35mm Tapcon Rod Hanger | 7.5mm | 35mm | 6mm | 50 |
| 16650 | M8x55mm Tapcon Rod Hanger | 7.5mm | 55mm | 6mm | 50 |
| 16651 | M10x55 Tapcon Rod Hanger | 7.5mm | 55mm | 6mm | 50 |

Rod Hanger Tapcon Vertical for Concrete the overhead threaded rod anchoring system







Fire protection - sprinkler systems, plumbing / Mechanical Contractors - air, water, hydraulics, Electrical Contractors

- conduit, cable trays, lighting, low voltage cabling, HVAC - unit heaters, A/C units, duct work, refrigeration, industrial maintenance - work in the rafters