



Visqueen Polyethylene DPC


Visqueen Polyethylene DPC is designed to prevent the passage of moisture in brick and block work from external sources.

Visqueen Polyethylene DPC is manufactured from high quality reprocessed materials to provide a cost effective and durable domestic grade DPC.

- Conforms to the requirements of BS 6515.
- Cost effective damp proof course for domestic construction.
- Embossed to assist mortar adhesion.
- Proven performance over many years.
- Manufactured from the highest quality reprocessed materials.
- Safe and clean to handle.

Sizes available: _____

DPCS100, 112.5, 150,225,300,337.5,350, 450,600 & 900



Visqueen Zedex CPT High Performance DPC

Visqueen Zedex CPT High Performance Damp Proof Course (DPC) and cavity tray system is manufactured from co-polymer thermoplastic (CPT) providing all the characteristics necessary for it to perform effectively for the lifetime of the building in which it is incorporated. Excellent performance under high compressive loads.

- Out performs all other high performance flexible DPC and cavity tray systems.
- Contains no hazardous phthalate or PVC plasticizers making it safe and clean to handle.
- System components for all applications including standard and bespoke Preformed cavity tray (cloak) units.
- Low permeability to Radon and Carbon Dioxide gas.
- BBA Certificate No.94/3059.

Sizes available: _____

DPCZ100, 150,225,300,350,450,500,600,750,900,1000



Visqueen Gas Resistant DPC

Visqueen Gas Resistant (GR) Damp Proof Course is a flexible polyethylene DPC with an aluminium foil designed to prevent the transmission of carbon dioxide, radon, methane and low level hydrocarbon vapours.

This is in addition to the product's usage as a damp proof course. Resistance to harmful gases is achieved by an integral aluminium film.

Sizes available: _____

GRDPC100,150,225,300,450,600,900,1000

- Integral aluminium foil for resistance to methane, radon, CO₂ and low levels of hydrocarbon vapours.
- Easy to apply using traditional methods.
- Use as part of an integral Gas Protection System.
- Independently assessed.



Visqueen GX Hydrocarbon DPC

Visqueen GX DPC is a blend of ethylene co-polymers suitable for use on brownfield sites that require protection from dangerous contaminants such as hydrocarbons and methane, together with excellent damp proofing properties. GX DPC is available in 30m lengths and in two widths, 645mm or 970mm

- Suitable for use on hydrocarbon contaminated sites.
- High puncture and tear resistance.
- Excellent chemical resistance.

Sizes available _____

GXDPC645 & 970



Visqueen Insulated Dpc

