

# UPVC WINDOW SCREWS

## CST-FURNITURE TO NON REINFORCED SECTION



- Diameter:- 4.2mm
- Length:- 19mm-35mm
- High performance coating to BS7412 : 2002
- Twin thread

CODE SIZE

CST 4.2 X 20MM  
25MM  
30MM  
35MM

## BAYPOLE SCREW



- Diameter:- 4.8mm
- Length:- 60mm-80mm
- Chrome 6 free
- Complies with BS7412 : 2002
- Suitable for reinforcement up to 2.5mm

CODE SIZE

BP 4.8 X 60MM  
70MM  
80MM

## LSS-FRICTION STAY TO NON REINFORCED SECTION



- Diameter:- 4.3mm
- Length:- 19mm-25mm
- High performance coating to BS7412 : 2002
- Locating lip under the head
- Twin thread

CODE SIZE

LSS 4.3 X 16MM  
19MM  
25MM

## CSH-FURNITURE TO NON REINFORCED SECTION



- Diameter:- 3.9/4.8mm
- Length:- 25mm-38mm
- High lo thread
- 4.8mm diameter is ideal as a repair screw

CODE SIZE

CSH 4.8 X 25MM  
38MM

## PSD-REINFORCEMENT SCREW



- Diameter:- 3.9mm
- Length:- 16mm-19mm
- Self tapping thread
- Complies with BS7412 : 2002
- Self drilling point

CODE SIZE

PSD 3.9 X 16MM  
19MM

## TSA -TRANSOM SCREW



- Diameter:- 4.8mm
- Length:- 65mm-95mm
- Part threaded
- High performance coating to BS7412 : 2002
- Self tapping thread, AB point

CODE SIZE

TSA 4.8 X 65MM  
80MM  
95MM

## CSD-REINFORCEMENT RETENTION



- Diameter:- 3.9mm
- Length:- 16mm-38mm
- Self tapping thread
- Self drill point

CODE SIZE

CSD 3.9 X 16MM  
19MM  
25MM  
32MM  
38MM