

TRANSFORMER

3KVA

PRODUCT SPECIFICATION

- 2 x 16amp 110 volt outlets
- 3000VA rating
- 1500VA continuous rating
- Tough GRP case
- 2M of cable
- Fitted 13A plug
- Reset button
- Class 1 construction
- Double wound with a secondary winding of 110v centre tapped earth, thus any fault on the secondary side cannot bring the user into contact with a voltage higher than 55v earth
- continuous rating 2/3 of total wattage, glass fibre box, 16A sockets
- Weight 16kg



5KVA Triple Outlet

PRODUCT SPECIFICATION

- 5 KVA Single Phase Transformer
- 5.0Kva Rating
- 3.0Kva Continuous rating
- 2 x 16amp outlets
- 1 x 32amp outlet
- Glass fibre box
- Resin filled
- Resettable circuit breaker
- 2M of cable
- Intermittent Duty: 5 minutes on/15 minutes off
- Fitted with 13amp 230v plug
- Approx weight 30kg



Transformer, Spider, 4 x 14M Leads - 110V

PRODUCT SPECIFICATION

Transformer:

- 2 x 16amp 110 volt outlets
- 3000VA rating
- 1500VA continuous rating
- Tough GRP case
- 2M of cable
- Fitted 13A plug
- Reset button
- Class 1 construction
- Double wound with a secondary winding of 110v centre tapped earth, thus any fault on the secondary side cannot bring the user into contact with a voltage higher than 55v earth
- continuous rating 2/3 of total wattage, glass fibre box, 16A sockets

Site Electrical Kit

