



ROOFGRIP SCREWS -FOR INSULATION TO METAL & TIMBER DECKING

*to steel decking 0.7-1.2mm thickness, or to timber decking

| Size | Diameter | MinBuild | Up Range | Max | Code |
|-------|----------|----------|----------|-------|--------|
| RG41 | 5.5MM | 13MM | | 26MM | 921191 |
| RG57 | 5.5MM | 13MM | | 42MM | 921192 |
| RG75 | 5.5MM | 26MM | | 60MM | 921193 |
| RG82 | 5.5MM | 26MM | | 67MM | 921195 |
| RG96 | 5.5MM | 26MM | | 81MM | 921196 |
| RG111 | 5.5MM | 42MM | | 96MM | 921186 |
| RG126 | 5.5MM | 58MM | | 111MM | 921187 |
| RG151 | 5.5MM | 83MM | | 136MM | 921188 |
| RG177 | 5.5MM | 83MM | | 162MM | 921189 |
| RG202 | 5.5MM | 108MM | | 187MM | 921190 |

Features

- 5.5mm diameter, high shear and tensile strength
- X point
- Modified butress thread – high pull-out resistance, reduced risk of stripping thread
- Resists cyclic action
- Low profile head reduces damage to underside of membrane
- Phillips No 3 recess – positive and safe drive system
- Grey speck coating – high corrosion resistance for long life
- UEATC & FM4470 approved



* to steel decking 0.7-1.2mm thickness, or to timber decking, or concrete decking

| Size | Diameter | MinBuild | Up Range | Max | Code |
|--------|----------|----------|----------|-------|--------|
| HRG38 | 6.3MM | 1MM | | 23MM | 921177 |
| HRG51 | 6.3MM | 19MM | | 36MM | 921178 |
| HRG76 | 6.3MM | 44MM | | 61MM | 921179 |
| HRG100 | 6.3MM | 68MM | | 85MM | 921168 |
| HRG127 | 6.3MM | 95MM | | 112MM | 921169 |
| HRG152 | 6.3MM | 120MM | | 137MM | 921170 |
| HRG176 | 6.3MM | 144MM | | 161MM | 921171 |
| HRG200 | 6.3MM | 168MM | | 185MM | 921172 |

Features

- 6.3mm diameter, high shear and tensile strength.
- X point.
- Modified butress thread – high pull-out resistance, reduced risk of stripping thread.
- Resists cyclic action
- Low profile head reduces damage to underside of membrane.
- Phillips No 3 recess – positive and safe drive system.
- Grey speck coating – high corrosion resistance for long life.
- UEATC & FM4470 approved.
- Stress plates available, see accessories.

FM APPROVED STRESS PLATES

| Size | Description | Code |
|---------|-----------------------------|--------|
| SP50 | 50MM ROUND GALVALUME METAL | 921198 |
| RG7575G | 75MM SQUARE GALVALUME METAL | 921194 |
| RGP80 | 80MM ROUND PLASTIC GEARLOCK | 921197 |

