

BLIND RIVET NUTS

Blind rivet nuts are the answer to many demanding fastening problems, providing a permanent reusable thread, accurately positioned even in thin materials. During installation the rivet nut body is designed to undergo a controlled deformation, creating a firm 360 degree upset, which grips the underside of the mounting surface. Rivet nuts can be used to join two or more materials together.

CSK HEAD ALUMIUM BLIND NUTS

SIZE	DRILL	GRIP	CODE
M4	5.6MM	0.25-1MM	ACN04-10
M4	5.6MM	1.00-2MM	ACN04-20
M4	5.6MM	2.00-3MM	ACN04-30
M5	6.6MM	0.25-2MM	ACN05-20
M5	6.6MM	2.00-3MM	ACN05-30
M5	6.6MM	3.00-4MM	ACN05-40
M6	8.6MM	0.25-1.5MM	ACN06-15
M6	8.6MM	1.50-3MM	ACN06-30
M6	8.6MM	3.00-4.5MM	ACN06-45
M6	8.6MM	4.50-6.0MM	ACN06-60

ROUND ALUMINIUM BLIND NUTS

SIZE	DRILL	GRIP	CODE
M4	5.6MM	1.7-2.5MM	ARN04-25
M4	5.6MM	2.5-4MM	ARN04-40
M4	5.6MM	4.0-5MM	ARN04-50
M5	6.6MM	1.7-3.5MM	ARN05-35
M5	6.6MM	3.5-4.5MM	ARN05-45
M5	6.6MM	4.5-5.5MM	ARN05-55
M6	6.6MM	1.7-3.0MM	ARN06-30
M6	6.6MM	3.0-4.5MM	ARN06-45
M6	6.6MM	4.5-6.0MM	ARN06-60
M6	6.6MM	6.0-7.5MM	ARN06-75

CSK HEAD BLIND NUTS

SIZE	DRILL	GRIP	CODE
M4	6.1MM	0.25-3MM	SCN04-30
M4	6.1MM	3.00-4.5MM	SCN04-45
M5	7.1MM	0.25-3MM	SCN05-30
M5	7.1MM	3.00-5.5MM	SCN05-55
M6	9.1MM	0.50-3MM	SCN06-30
M6	9.1MM	3.00-5.5MM	SCN06-55
M6	9.1MM	5.50-8MM	SCN06-80
M8	11.1MM	0.50-3MM	SCN08-30
M8	11.1MM	3.00-5.5MM	SCN08-55
M8	11.1MM	5.50-8MM	SCN08-80

ROUND HEAD BLIND NUTS

SIZE	DRILL	GRIP	CODE
M4	6.1MM	1.7-3.5MM	SRN04-35
M4	6.1MM	3.5-5.0MM	SRN04-50
M5	7.1MM	1.7-4.0MM	SRN05-30
M5	7.1MM	4.0-6.5MM	SRN05-55
M6	9.1MM	1.7-4.5MM	SRN06-30
M6	9.1MM	4.5-6.0MM	SRN06-55
M6	9.1MM	6.0-8.0MM	SRN06-80
M8	11.1MM	1.7-4.5MM	SRN08-45
M8	11.1MM	4.5-6.5MM	SRN08-65

CSK STAINLESS BLIND NUTS

M4	6.1MM	0.5-2MM	SSCN4-20
M4	6.1MM	2.0-3.5MM	SSCN4-35
M5	7.1MM	0.5-3.0MM	SSCN5-30
M5	7.1MM	3.0-5.0MM	SSCN5-50
M6	9.1MM	0.5-3.0MM	SSCN6-30
M6	9.1MM	3.0-5.5MM	SSCN6-55
M8	11.1MM	0.5-3.0MM	SSCN8-30
M8	11.1MM	3.0-5.0MM	SSCN8-50

ROUND STAINLESS BLIND NUTS

M4	6.1MM	1.2-3.0MM	SSRN4-30
M5	7.1MM	1.2-3.5MM	SSRN5-35
M6	9.1MM	1.7-4.5MM	SSRN6-45
M8	11.1MM	1.7-4.5MM	SSRN8-45
M8	11.1MM	4.5-6.5MM	SSRN8-60

- other threads and diameters available to order
- slim head available in alum, steel & stainless
- Ribbed shank, hexagon, closed all available to order
- Full range of hand & battery operated tools available




SPECIALIST BLIND NUTS & TOOLING FOR ALL.

JACK NUTS-Threaded insert for all materials

HOLE SIZE SIZE	MIN		MAX		CODE
	MIN	MAX	MIN	MAX	
M4X0.7	8.08	8.38	0.4MM	4.75MM	M4-SN
M4X0.7	8.08	8.38	4.75MM	9.53MM	M4-LN
M5X0.8	9.7	10.16	0.4MM	4.75MM	M5-SN
M5X0.8	9.7	10.16	4.75MM	9.53MM	M5-LN
M6X1.0	11.13	11.43	0.4MM	4.75MM	M6-SN
M6X1.0	11.13	11.43	4.75MM	9.53MM	M6-LN
M6X1.0	11.13	11.43	9.53MM	12.70MM	M6-XLN

The Jacknut threaded insert is an economical blind fastener designed for assembly-line use in thin, soft or brittle materials. When tightened, the body collapses to form legs which grip the inside of the mounting surface, leaving a permanent, re-useable threaded insert.



TOOLING FOR RIVETNUTS & JACKNUTS

Type		Code
HAND 1	SUITABLE FOR M3-M5 STEEL & ST/ST M3 - M6 IN ALUMINIUM	HRNT1
HAND 2	SUITABLE FOR M4 - M12 LIGHT USAGE	DFS211T
LEVER TYPE	SUITABLE FOR M5 - M10 ALUM & STEEL M8 IN STAINLESS	LRNT1A
BATTERY TYPE	BATTERY OPERATED RIVNUT TOOL SUITABLE FOR M4 - M6 IN STAINLESS, M4 - M8 STEEL & M4 - M10 ALUMINIUM	FIRE1A
JACKNUT TOOL	SUITABLE M4 - M6 JACKNUTS	JN1

