

Split Nylon Frame Anchor

Long expansion copes with hollow brickwork. A pre-assembled through fixing for battening and framework where alignment or distortion

Code	Description	Anchor Ø	Length	Max Fixture	Box Qty
NFA8X60	Nylon Frame anchor	8mm	60mm	15mm	50
NFA8X80	Nylon Frame anchor	8mm	80mm	35mm	50
NFA8X100	Nylon Frame anchor	8mm	100mm	55mm	50
NFA8X120	Nylon Frame anchor	8mm	120mm	75mm	25
NFA10X80	Nylon Frame anchor	10mm	80mm	30mm	25
NFA10X100	Nylon Frame anchor	10mm	100mm	50mm	25
NFA10X115	Nylon Frame anchor	10mm	115mm	65mm	20
NFA10X135	Nylon Frame anchor	10mm	135mm	85mm	20
NFA10X160	Nylon Frame anchor	10mm	160mm	110mm	20



Substrates

Concrete, stone, solid block, solid brick

Countersunk sleeve and screw allows flush finish
Zinc plated drive screw for corrosion resistance (dry internal use)
Nylon sleeve assists shear capacity
Through fixing lowers in place cost

Wall plates, sole plates, battens, door & window frames



Façade fixing anchors csk and hex

Code	Description	Anchor Ø	Length	Max Fixture	Box Qty
SXS1080T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	80mm	30mm	50
SXS10100T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	100mm	50mm	50
SXS10120T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	120mm	70mm	50
SXS10140T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	140mm	90mm	50
SXS10X160T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	160mm	110mm	50
SXS10X180T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	180mm	130mm	50
SXS10X200T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	200mm	150mm	50
SXS10X230T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	230mm	180mm	50
SXS10X260T	Csk Nylon Façade Anchor Galvanised T40 recess	10mm	260mm	210mm	50
SXS1060FUS	Hex Nylon Façade Anchor Galvanised	10mm	60mm	10mm	50
SXS1080FUS	Hex Nylon Façade Anchor Galvanised	10mm	80mm	30mm	50
SXS10100FUS	Hex Nylon Façade Anchor Galvanised	10mm	100mm	50mm	50
SXS10120FUS	Hex Nylon Façade Anchor Galvanised	10mm	120mm	70mm	50
SXS10140FUS	Hex Nylon Façade Anchor Galvanised	10mm	140mm	90mm	50
SXS10160FUS	Hex Nylon Façade Anchor Galvanised	10mm	160mm	110mm	50
SXS10180FUS	Hex Nylon Façade Anchor Galvanised	10mm	180mm	130mm	50



*** all sizes above available in stainless steel

Approved for:

Concrete
Solid brick
Solis sand-lime brick
Hollow block made from lightweight concrete
Multilayer composite concrete wall

Also suitable for:

Natural stone with dense structure
Solid block made from lightweight concrete
Solid panel made from gypsum

For fixing of:

Railings
Handrails
Gates
Door frames
Façade and roof substructures made of wood and metal
Fire protection doors
Windows
Kitchen cabinets
Squared timbers
Facings
Cable conduits

