

Tanking Membranes


Visqueen Self Adhesive Membrane (SAM)

Visqueen Self Adhesive Membrane is a BBA Accredited self adhesive waterproofing system.

It can be used as a tanking or damp proof membrane for both horizontal and vertical applications. borne alkalis present in some mortar and concrete. Visqueen Self Adhesive Membrane prevents the ingress of water and associated water-

Self Adhesive waterproofing membrane for above and below ground applications.

Tough, high performance, high density polyethylene membrane provides resistance to puncture and tearing. Use with unique Visqueen HP Tanking Primer to obtain best adhesion.



Visqueen Gas Resistant Self Adhesive Membrane

Visqueen Gas Resistant (GR) Self Adhesive Membrane is designed to prevent the transmission of carbon dioxide, radon and methane gases in tanking applications or where hydrostatic pressure is present.

Resistance to gas is achieved by an integral aluminium film.

Substrates should be primed with Visqueen HP Tanking Primer prior to application.

Visqueen Gas Resistant (GR) Self Adhesive Membrane is compatible with Visqueen Gas Resistant (GR) DPC and other Visqueen Gas Membranes.

Self Adhesive waterproofing membrane for above and below ground applications.

Superior adhesion.

Integral aluminium foil for resistance to methane, radon and carbon dioxide.



Visqueen TorchOn Tanking Membrane

Visqueen TorchOn Tanking Membrane is a robust waterproofing membrane,

Visqueen TorchOn Tanking Membrane can be used both vertically and horizontally above and below ground level to prevent the ingress of water.

Robust waterproofing membrane for above & below ground waterproofing applications.

Torch bonded laps provide a homogeneously sealed junction.

Ideal for cold weather application.

Used to waterproof basements, lift pits, reinforced concrete Slabs, retaining walls



Visqueen GX Pre Applied Membrane

Visqueen GX Pre Applied Membrane is an advanced high performance, flexible HDPE geomembrane.

The membrane has a textured face on one side designed to aid adhesion to cast concrete.

The membrane is 1.5mm thick and supplied in roll form 2.95m x 25m.

Heavy duty, high performance membrane.

Joints can be tape bonded or welded.

Suitable for both damp proofing and tanking applications.

Barrier to hazardous ground gases.

Barrier to hydrocarbon contamination.

Specified for major projects throughout the UK.



Visqueen Protect&Drain

Visqueen Protect&Drain consists of a geotextile filter membrane thermally bonded to a cusped HDPE core.

The product is 6mm thick and supplied in rolls 1.1m x 50m.

Rapid installation.

High puncture resistance protection.

High flow capacity to alleviate hydrostatic pressure on below ground structures.



Visqueen Urban Drainage Geomembrane (UDG)

Visqueen UDG Membrane is a UK manufactured co-polymer thermoplastic membrane.

The product is black, 500 microns thick (2000 gauge) and supplied in rolls 4m x 12.5m.

Part of the Visqueen Urban Drainage Geomembrane (UDG) System

Impervious membrane for permeable paving systems

Also suitable for underground stormwater storage systems

High resistance to puncture

Restricts water entering the sub-grade

Preserves sub-grade structural integrity

Installed with tape bonded or welded joints

Manufactured in the UK

