

TIMBERFIX PREMIUM WOODSCREWS

Shank ribs to reduce drive torque
 Innovative thread geometry ~ reduced splitting
 German lubricant system
 Packed in two part box with window



CODE	DIAM	LENGTH	BOX
YCS3.5X15TF	3.5mm -6g	15mm	200
YCS3.5X20TF	3.5mm -6g	20mm	200
YCS3.5X25TF	3.5mm -6g	25mm	200
YCS3.5X30TF	3.5mm -6g	30mm	200
YCS3.5X40TF	3.5mm -6g	40mm	200
YCS3.5X50TF	3.5mm -6g	50mm	200
YCS4X16TF	4mm-8g	16mm	200
TCS4X20TF	4mm-8g	20mm	200
YCS4X25TF	4mm-8g	25mm	200
YCS4X30TF	4mm-8g	30mm	200
YCS4X35TF	4mm-8g	35mm	200
YCS4X40TF	4mm-8g	40mm	200
YCS4X45TF	4mm-8g	45mm	200
YCS4X50TF	4mm-8g	50mm	200
YCS4X60TF	4mm-8g	60mm	200
YCS4X70TF	4mm-8g	70mm	100
YCS5X30TF	5mm-10g	30mm	200
YCS5X40TF	5mm-10g	40mm	200
YCS5X50TF	5mm-10g	50mm	200
YCS5X60TF	5mm-10g	60mm	100
YCS5X70TF	5mm-10g	70mm	100
YCS5X80TF	5mm-10g	80mm	100
YCS5X90TF	5mm-10g	90mm	100
YCS5X100TF	5mm-10g	100mm	100
YCS6X50TF	6mm-12g	50mm	100
YCS6X60TF	6mm-12g	60mm	100
YCS6X70TF	6mm-12g	70mm	100
YCS6X80TF	6mm-12g	80mm	100
YCS6X90TF	6mm-12g	90mm	100
YCS6X100TF	6mm-12g	100mm	100
YCS6X130TF	6mm-12g	130mm	100
YCS6X150TF	6mm-12g	150mm	100