AdhesivesRange





Gripbond SF

Offering less impact on the environment this solventfree, advanced technology formula offers instant grab and a tough permanent bond on virtually any porous or non-porous surface. Gripbond SF is a low odour, water clean up, construction adhesive which cures to form a high strength bond. Extremely low VOC content, contains no harmful raw materials, making it safer for the environment, safe for the user and safe on substrates.

Note: Recommended for internal use only.

NEW IMPROVED FORMULATION

Application: Ideal for fixing panelling, plasterboard, cove pase, window sills, styrofoam, carpet tack strips, aluminium firring strips, tub surrounds, fireplaces, loose floor/wall tiles, plywood, aluminium, steel, wood, concrete, cork, general repairs to wood, fixing hardboard and plywood and as a neneral adhesive

BDPGE

BDA007

Aerosol Spray Adhesive

Gives exceptionally strong adhesion for a wide range of demanding uses. Fitted with a variable discharge spray that controls the width of the fan.

Application: It is ideal for perimeter bonding of carpet tiles and minor flooring installations, and for use in the furniture and automotive industries, especially for bonding foam non-structural applications where a high strength bond is

Beige

Gripbond

A multi-purpose, synthetic rubber based construction adhesive that can replace mechanical fixings in a wide variety of domestic commercial and industrial applications. A fast bonding, non-slumping, instant grab adhesive with good gap-filling properties even on uneven surfaces. It can be used in all weather conditions and is suitable for rough and porous surfaces. It can also be over-painted once dry.

Application: Ideal for fixing a wide variety of materials. It can be used to fix skirting boards, door surrounds and frames, window sills, all types of cladding, wall battens, decorative wall boards, metal carpet edges, automotive trims and much more. It can be used for interior and exterior applications.

Note: this product is Toluene free!

BDGB12

BDGB



Boxed in a striking merchandising carton for added display impact and easy dispensing.

UICE

FRAB

UICH

AdhesivesRange



Contact Adhesive

A premium grade, solvent-based, neoprene adhesive with high grab and long open time to enable re-positioning. Easily applied (500ml and 1L containers come complete with handy brush applicator).

Application: Can be used for bonding to cork, leather, rubber, metals, wood, chipboard, hardboard, laminated plastics (e.g. Formica), dense textiles, plaster, stone, concrete cementitious screeds and smoothing compounds. It will bond rigid PVC and PVCu sheets but the materials should be checked for suitability prior to application as plasticiser

Note: This product is not suitable for polystyrene, polythene, polypropylene, silicone rubbers, bitumen or PTFE. The solvent in the contact adhesive may attack certain painted or lacquered surfaces. Test a small area of adhesive on the surfaces prior to full application. 5L lever lid tin now available.

Duo "2 in 1" Wood Glue

Developed using the latest fast drying, water resistant, PVA technology, this product achieves a bond strength stronger than the wood itself. A cost-effective, water-resistant wood adhesive that conforms to the requirements of category D3/3 and D3/4 of EN204. In addition, it also meets the resistance to sustained load (creep test) requirements of BS 4071 "Polyvinyl Acetate (PVA) Emulsion

Application: Designed as a one-pack, ready-to-use adhesive which gives a fast rate of bond strength development. Suitable for hard and soft woods, decorative laminates, chipboard blockwood and other engineered timber panels. Can be used in applications where joints may be subjected to short term water contact or exposure to high humidity i.e. kitchen work surfaces, window frames, doors and stairs. Suitable for interior & exterior applications.

Product Codes: BDA050, BDA051, BDA052 BDA053 BDA054, BDA055, BDA056, BDA057

White



17

Page Contents:

AdhesivesRange



A one part, high quality, high modulus sealing and bonding material based on MS polymer technology. A totally neutral "hybrid" sealant for use in areas requiring a tough elastic rubber ioint or as an adhesive with superior bonding. strength. Conforms to ISO11600-20-HM.

Properties

- High modulus, remains permanently
- For sealing and bonding interior and exterior applications in all weather conditions
- Can be over-painted with waterbased paints (alkyd resin based paints may slow down drying process - test a small area before application.)
- Non staining (excellent for use on natural stone).
- Non shrinking
- Contains no isocyanates, solvents, silicone and phalates Rapid curing.
- Resistant to UV radiation, water (including sea water), mould and chlorine.
- Excellent adhesion to most surfaces (even moist surfaces)
- Will not discolour surfaces.
- Wet on wet application.

Application: GRIPBOND PRO can be used:

- For filling and sealing of connecting joints. cracks, holes, etc in the building sector. For wooden joints in ship decks.
- For bonding metal to metal
- As a high quality glazing sealant including for use with burglar safe glazing systems
- As a universal waterproof construction adhesive for bonding stone, concrete, mirrors (with an acetone resistant backing), natural stone, marble, gypsum board, polycarbonates, polystyrene, PVC. many plastics, ceramics, copper, lead, zinc, aluminium, stainless steel, wood and glass

dark conditions or poor light the product may yellow.

Note: This product is not recommended for use with expansion joints or for

tions where the joints are continually immersed in water. If allowed to cure in

Mega Stick Polyurethane Construction Adhesiv

A fast curing, adhesive foam that has been specially developed for the rapid installation of plasterboard, insulation boards, floorboards and roof decking. Supplied in an aerosol can, the product can be used with a standard foam gun. A multi-purpose, polyurethane construction adhesive in a can - but not just a drywall adhesive. The cured adhesive is an excellent heat insulator and has exceptionally good adhesion properties.

Application: Adheres well to most building materials, with e exception of Teflon, polyethylene and silicone surfaces. Suitable for installing doors and windows, insulating and ixing pipes, filling holes and gaps, fixing wall panels, skirting boards, roof tiles, decking and for thermal insulation.

No mixing, no mess, no water, no dust! No need to carry heavy bags of plaster.

Can also be used to dampen sound.

- One can fixes approxiamately 5 standard plaster boards. 30% time saving over conventional dry wall adhesives.

bond it

BDMSPWH

BDMSPBI

BDMSPGR

- Can be applied direct to boards or the wall.
- Can Works on solid walls, metal and timber studding.

Product Codes: BDEFMS



MEGA

NOT JUST A

Contractors Grade PVA

An all purpose, premium quality primer, sealer and bonding agent that dries quickly to a high bond strength.

Application: Can be used with plaster, ement, timber, gypsum wall boards and paper. Properties as an adhesive include fast rying. It is also a readily dilutable primer for ealing applications or addition to cement and plaster to improve adhesion and cure.

- High solids content compared with other contractor grades.
- Solids content is all polymer
- Better adhesion and flexibility.



Product Codes: BDAC1, BDAC5, BDAC25, BDAC200

Product Codes: BDA021, BDA022, BDA023, BDA024, BDA025, BDA026

PVABOND

PVA Adhesive & Sealer

A high performance sealer primer dust-proofer and bonding agent. Improves adhesion and reduces cracking in cements and plaster. Primes and seals porous surfaces. Quick drying, durable and has a very high bond strength. Conforms to

Application:

- Plaster primer, porous surface primer and sealer
- Rendering key coat for internal applications.
- General purpose adhesive for bonding all

and threadlocker. Used as a locking compound for direct application to lightly oiled components. Replaces spring washers and lock nuts. Removable using the correct tools. Also prevents rusting or corrosion. Non-drip

BIA4350

AdhesivesRange

HVC Cyanoacrylate Superglue

A premium cyanoacrylate adhesive developed for bonding rubber and plastics including PVCu. A high viscosity superglue for use on porous surfaces. Also has gap-filling properties making it ideal for bonding trims and caps on PVCu windows as well as rubber, wood, metal, ceramics, leather, porcelain and card. Comes with a resealable cap.

bond iii



DISPLAY HIGH STRENGTH **BOXES** SUPERGLUES



RGC Cyanoacrylate Superglue

A medium viscosity superglue. Fast setting at room temperature and is economical to use. Suitable for close



A70 Studlock

A high strength, anaerobic adhesive for the permanent retention and sealing of threaded fasteners, sleeves and bearings. It is resistant to fuels, oils, hydraulic & refrigeration fluids. Also acts as a lubricant during assembly to ensure accurate torquing and protection against corrosion. Prevents rusting or corrosion and cannot be dismantled once adhesive has set.



A43 Threadlock

A medium viscosity, medium strength screw consistency for clean, economic application.



PU Wood Glue

One-part moisture cure polyurethane adhesives specially formulated for waterproof bonding. These products are seawater proof and are resistant to acid and chemicals. Conforms to BS EN 204 (Class D4).

- GEL FORMULATION: A solvent-free, rapid setting thixotropic translucent PU ael which sets in 5 minutes.
- LIQUID FORMULATION: A solventfree, rapid setting brown liquid PU adhesive which sets in 30 minutes.

Application: Excellent bonding properties uitable for all wood products including andwich panels and insulation materia to most common substrates. Suitable for



Transparent

Cyanoacrylate Accelerator

Accelerates the rate of cure of cvanoacrylate adhesives Improves bonding to difficult surfaces and prevents penetration of adhesive into porous materials. Speeds strength development.



Mitre Kit Adhesive

A high strength bonding system comprising a cyanoacrylate adhesive with an aerosol activator to ensure full and rapid curing on acid surfaces. Can be used for bonding MDF, wood, rubber and most plastics. Pack includes: 1 tin of Activator (200ml) and 1 bottle of HVC Superglue (50a).



Silicone Release Spray

Has a wide range of uses including mould releasing and lubrication in the automotive, engineering, food, clothing and upholstery industries, where the clean, low toxicity lubricating properties of silicone are ideal.



Multi-Purpose Spray Lubricant

A low viscosity solvent and oil blend, giving excellent penetrating properties. It is a high performance, multi-application fluid which has excellent de-watering, anti-corrosive and general lubricating properties.



19