

## Slipsafe FR™

SlipSafe FR™ is a large area floor protection film specially granulated to give a non abrasive, anti slip surface. The granulation is encased in the core material so is safe to use on finished surfaces without fear of abrasion or scratching. It also provides added grip and anti-slip properties to this economical floor protector which is waterproof and flame retardant.

- **QUICKLY APPLIED**

Simply roll out cut to length and join with tape where required.

- **FIXING**

Secured using the appropriate adhesive tape, increased grip to carpets can be achieved by adding our Self Adhesive Velcro.

- **INCREASED SLIP RESISTANCE**

Granulated materials creates an excellent anti slip surface.

- **INDUSTRIAL STRENGTH**

Puncture and tear resistant.

- **WATERPROOF**

Provides a complete barrier against spills and wet foot traffic.

- **AVAILABLE IN TWO GRADES**

Achieves the correct degree of protection for your project.

- **FLAME RETARDANT**

Tested to European Standard manufactured under ISO 9001:2000



| code      | description                           | size      |
|-----------|---------------------------------------|-----------|
| SLIPFR200 | 125micron Standard FR slipsafe roll   | 1.5mx200m |
| SLIPFR100 | 250micron Industrial FR slipsafe roll | 1.5mx100m |

## Protecta Fleece™

Protecta Fleece™ is a waterproof, impact resistant 'roll out' protection and being self adhesive requires no additional taping or fixing to stay in place. It is supplied in rolls and therefore unlike other impact protection products is easily transported and manoeuvred on site.

- **QUICKLY APPLIED**

Simply roll out, smooth into place and trim.

- **FIXING**

Stays securely in place, does not require tape or additional fixing.

- **STAYS IN PLACE**

Being self adhesive, once applied Protecta Fleece™ doesn't ruck or travel.

- **LEAVES NO RESIDUE**

Special technology ensures that the adhesive remains on the product and doesn't transfer to the protected surface upon removal.

- **IMPACT RESISTANT**

Thick fibre layer creates excellent impact protection.

- **WATERPROOF**

100% waterproof, holds spills and protects against wet foot traffic.

- **FLAME RETARDANT**

Protecta Fleece™ is available in Standard (Non FR) and Flame Retardant tested to:

ISO4589-2: 1996 Oxygen Index prEN2825 & prEN2826, BS476: Part 12: 1991 Ignition Source C and Large Flame Test to LPS 1207: 1994 Section 3.1.3



| code    | description                         | size    |
|---------|-------------------------------------|---------|
| PF50NF  | Non Fire Rated self adhesive Fleece | 50mtrx1 |
| PF100NF | Non Fire Rated self adhesive Fleece | 50mtrx2 |
| PF50F   | Fire Rated self adhesive Fleece     | 50mtrx1 |

## CARPET PROTECTION

### Protecta Carpet™

With over 1 million square metres sold every year Protecta Carpet™ is a tried, tested and proven, effective self adhesive carpet protection film. Applied freehand or with specially made applicators it can be laid in single strips as a 'runner' or installed across a whole carpeted surface to provide a waterproof barrier which protects from spills, dirt and contamination from foot traffic. With health and safety in mind Protecta Carpet™ stays securely in place and doesn't travel like dust sheets or loose protection methods making it ideal for use in public areas. Protecta Carpet™ is only suitable for use on carpet.

- **QUICKLY APPLIED**

Either use our specially designed applicators or roll out and smooth into place by hand.

- **FIXING**

Self adhesive, does not require tape or additional fixing.

- **STAYS IN PLACE**

Being self adhesive, once applied Protecta Carpet™ doesn't ruck or travel avoiding trip hazards.

- **LEAVES NO RESIDUE**

Special technology ensures that the adhesive remains on the product and doesn't transfer to the carpet upon removal.

- **INDUSTRIAL STRENGTH**

Puncture and tear resistant.

- **WATERPROOF**

Stops contamination from spills and wet foot traffic.

- **HYGIENIC**

Can be swept or hoovered prior to removal, avoids the spread of contamination.

- **AVAILABLE IN TWO GRADES & SEVEN DIFFERENT ROLL SIZES**

Enabling you to cover the right area with the correct degree of protection.

- **FLAME RETARDANT**

Tested to BS 4790 (carpet flammability).



| code      | description                        | size          |
|-----------|------------------------------------|---------------|
| CP60025   | Standard Clear Carpet Protection   | 600mmx25mtr   |
| CP600100  | Standard Clear Carpet Protection   | 600mmx100mtr  |
| CP800100  | Standard Clear Carpet Protection   | 800mmx100mtr  |
| CP1200100 | Standard Clear Carpet Protection   | 1200mmx100mtr |
| CPH60025  | Heavy Duty Clear Carpet Protection | 600mmx25mtr   |
| CPH60050  | Heavy Duty Clear Carpet Protection | 600mmx50mtr   |
| CPH120050 | Heavy Duty Clear Carpet Protection | 1200mmx50mtr  |



### Protecta Carpet™ Dispenser

|          |                      |        |
|----------|----------------------|--------|
| DISP600  | Dispenser for 600mm  | 600mm  |
| DISP1200 | Dispenser for 1200mm | 1200mm |



## Carpet Guard FR™

Carpet Guard FR™ has been specifically created for use in sensitive areas where potential slip and fire hazards are increased.

Using the same adhesive technology as Protecta Carpet™ it will not ruck or travel when applied but also removes clean, leaving no residue. Being embossed it creates an anti-slip surface and provides increased protection from foot traffic, spills, etc.

Carpet Guard FR™ is only suitable for use on carpet.

- **QUICKLY APPLIED**

Either use our specially designed applicators or roll out and smooth into place by hand.

- **FIXING**

Self adhesive, does not require tape or additional fixing.

- **STAYS IN PLACE**

Being self adhesive, once applied Carpet Guard FR™ doesn't ruck or travel.

- **LEAVES NO RESIDUE**

Special technology ensures that the adhesive remains on the product & doesn't transfer to the carpet upon removal.

- **INDUSTRIAL STRENGTH**

Puncture and tear resistant.

- **INCREASED SLIP RESISTANCE**

Embossed surface provides excellent slip resistance.

- **WATERPROOF**

Stops contamination from spills and wet foot traffic.

- **HYGIENIC**

Can be swept or hoovered prior to removal, avoids the spread of contamination.

- **FLAME RETARDANT**

Tested to BS EN ISO 4589-2: 1999 (Oxygen Index) Tested to prEN2824, prEN2825 & prEN2826 (Smoke and Toxicity) Tested to BS476: Part 12: 1991 Ignition Source C (Ignitability) Tested to Large Flame (Burning Droplets and Vertical Flaming)



| code          | description             | size          |
|---------------|-------------------------|---------------|
| CGUARD60025   | Fire Rated Carpet Guard | 600mmx25mtr   |
| CGUARD600100  | Fire Rated Carpet Guard | 600mmx100mtr  |
| CGUARD1200100 | Fire Rated Carpet Guard | 1200mmx100mtr |



## PWFR™

PWFR™ is woven, coated, flame retardant polypropylene floor protector. Being woven it has amazing strength, durability and tear resistance.

Excellent in high traffic areas and is ideally suited for the protection of carpets and soft flooring surfaces. Supplied in 2m wide rolls PWFR™ is deployed very quickly and will protect most floor surfaces from dust, light debris, dirt, spills and wet foot traffic.

- **QUICKLY APPLIED**

Simply roll out, cut to length and join with tape where required.

- **FIXING**

Secured using the appropriate adhesive tape.

- **INCREASED SLIP RESISTANCE**

Coated surface provides increased slip resistance.

- **INDUSTRIAL STRENGTH**

Woven material immensely increases strength.

- **WOVEN**

Amazing tear resistance.

- **WATERPROOF**

Provides a complete barrier against spills and wet foot traffic.

- **CUSTOMISATION**

We can add your company logo and contact details.

- **FLAME RETARDANT**

PWFR™ is available in either Flame Retardant, tested to BS EN ISO 4589-2:1999 (Oxygen Index), prEN2824, prEN2825 and prEN2826 (Smoke & Toxicity), BS476: Part 12: 1991 Ignition Source C (Ignitability) and Large Flame (Burning Droplets and Vertical Flaming) or Flame Retardant Certified to LPS 1207.



| code      | description                          | size      |
|-----------|--------------------------------------|-----------|
| PWFR200   | 125micron Flame Retardant            | 100mtrx2m |
| PWFR200LP | 125micron Flame Retardant to LPS1207 | 100mtrx2m |

