








| Rytons<br>Order/Specification<br>Code  | Main Uses,<br>Features and Benefits   | Size   | Free<br>Area       | Colours                          | Approvals<br>& Testing  |
|--|---|--|--------------------|----------------------------------|---|
| Code: RYTWEEP<br>    | <b>Rytons Rytweep®</b><br>Unobtrusive cavity weep hole.<br>Virtually unseen when installed; shows only small weep outlet.<br>Lugs aid mortar adhesion.<br>Quickly and easily fitted.  | 101mm L x<br>66mm H x<br>10mm W                              | Not applicable     | B/S, TC,<br>Clear,<br>new GR     | <p style="text-align: center; color: purple; font-weight: bold;">new colour</p> |
| Code: RYWTUBE<br>    | <b>Rytons Rytweep® Tube</b><br>Extension for blockwork and rendered walls.<br>Push fit into Rytons Rytweep®.<br>Easily cut to length.   | 500mm L x<br>6mm Int. Dia. x<br>8mm Ext. Dia.                | Not applicable     | Clear                            |   |
| Code: WEEPW-<br>    | <b>Type W Weep Vent</b><br>The type W is the first specifically conceived dual-purpose weep & vent.<br>Aesthetically & practically designed with a functionally inclined front.<br>The type W is finished with an insect resistant grill  | 105/115mm L<br>x 65mm H x<br>10mm W                          | Not applicable     | GR, BL,<br>TC,WH,BS              |   |
| Code: RTV250CL<br> | <b>Rytons Retro Weep Vent</b><br>Retro-fit cavity ventilator and weep hole duct.<br>Ideal solution when no provision has been made for cavity venting or weeps or an insufficient number have been installed.<br>External fins provide a lock-tight fit.<br>Flange covers drilling for a neat finish.<br>Clear colour blends with any facing brick or render.<br>Use in timber frame and traditional build. | 80mm L<br>(excl. flange)<br>x 26mm Dia.<br>(inc. fins)       | 250mm <sup>2</sup> | Clear                            | <p style="text-align: center; color: purple; font-weight: bold;">new</p>        |
| Code: SVFMIN<br>   | <b>Rytons Flyscreened Slim Vent® Minor</b><br>Flyscreened cavity ventilator.<br>Use in timber frame and traditional build.<br>An effective weep hole.<br>Internal baffles prevent water transfer.<br>No special fixing or brickwork required.<br><br><b>Rytons Slim Vents® are the ONLY timber frame vents with BBA approval!</b>   | 103mm L x<br>66mm H x<br>10mm W<br>Allows 6mm<br>venting gap | 220mm <sup>2</sup> | GR, BL,<br>B/S, TC,<br>WH, Clear |   |

**Colour Key**



# Multifix® Air Bricks and Periscope® Underfloor Ventilator

| Rytons<br>Order/Specification<br>Code  | Main Uses,<br>Features and Benefits  | Size  | Free<br>Area                                  | Colours                               | Approvals<br>& Testing  |
|--|--|---|---|---------------------------------------|---|
| Code: SVMAJ<br>      | <b>Rytons Slim Vent® Major</b><br>Extra long cavity ventilator.<br>Also cross-cavity and underfloor ventilator.<br>Two sets of baffles prevent water transfer.<br>No special fixing or brickwork required.   | 304mm L x<br>66mm H x<br>10mm W<br>Allows 6mm<br>venting gap                      | 330mm <sup>2</sup>                            | Clear                                 |   |
| Code: MFAB96<br>     | <b>Rytons '9x6' Multifix® Air Brick</b><br>Robust interlocking '9x6' air brick.<br>Textured finish maintains aesthetic appearance.<br>Use with Rytons '9x6' Telescopic AirLiner® (TCL18000)<br>and '9x6' Acoustic AirLiner® (TAL8000).<br>U.V. stabilised to protect against fading by sunlight.                                   | 215mm L x<br>134mm H x<br>59mm D  | 15185mm <sup>2</sup><br>151.85cm <sup>2</sup> | B/S, TC                               |  U.V. stabilised   |
| Code: MFAB<br>      | <b>Rytons Multifix® Air Brick</b><br>Robust interlocking air brick.<br>One size can form a unit '9x6', '9x9' etc.<br>Textured finish maintains aesthetic appearance.<br>Use with Rytons Periscope® Underfloor Ventilator<br>(PUFV) and AirLiners® 9x3', '9x6' and '9x9'.<br>U.V. stabilised to protect against fading by sunlight. | 215mm L x<br>66mm H x<br>58mm D   | 7750mm <sup>2</sup><br>77.5cm <sup>2</sup>    | GR, BL,<br>B/S, TC,<br>WH, BR,<br>B/B |  U.V. stabilised |
| Code: PUFV<br>     | <b>Rytons Periscope® Underfloor Ventilator</b><br>For block and beam and timber floors.<br>Alleviates build-up of dangerous gases.<br>Expands up to 5 brick courses.<br>Prevents damage by condensation.<br>Use with Rytons Multifix® Air Brick (MFAB).  | 218mm W x<br>250mm D x<br>368mm H<br>Fully extended<br>with MFAB fitted           | 7750mm <sup>2</sup><br>with MFAB<br>fitted    | BL                                    |   |
| Code: PUFVEXT<br>  | <b>Rytons Periscope® Vertical Extension</b><br>Vertical extension for Rytons Periscope® Underfloor<br>Ventilator (PUFV).<br>Easily installed with no extra fitting required.<br>May be cut to length.  | 1000mm L x<br>220mm W x<br>54mm D   | Not<br>applicable                             | BL                                    |   |
| Code: HADAP100<br> | <b>Rytons Horizontal Adaptor</b><br>Allows a connection from Rytons Non-Telescopic<br>AirLiner® (TCL8LNR) to flexible or rigid ducting.<br>Allows a connection from Rytons Periscope®<br>Underfloor Ventilator (PUFV) to rigid ducting e.g. soil<br>pipe for ventilation to isolated floor areas.                                  | 215mm L x<br>67mm H x<br>49mm D excl.<br>tube connector<br>x 101mm Dia.<br>spigot | 5980mm <sup>2</sup><br>59.8cm <sup>2</sup>    | BL                                    |   |