



Kit Contains:

Spit Pulsa 700E Cordless Gas Nailer, high impact carry case, 2 x batteries, battery charger, safety glasses to EN166:F, allen key, dust cover and instruction manual.

Applications

Cable Management

- Skirting and dado trunking systems
- Mini trunking systems
- Metal trunking systems
- Low voltage cabling and temporary lighting
- Metal and plastic capping
- Fire resistant cabling systems (Prysmian Firefix™)

Wiring Accessories

- Metal back boxes
- PVC - U back boxes
- PVC - U conduit
- Steel conduit
- Junction boxes
- Switch boxes
- Smoke detectors

TIP

For overhead electrical fixing applications why not try the Spit PulsaLift pole tool. Refer to page 81.

HC6 Pins, Flush Head - Hard Concrete and Steel Substrates



Hard concrete and steel pins, with collation that fragments on impact to leave the pin 'flush' to the fixed article. Use with Prysmian Firefix™. Available in sizes from 15 - 27mm.

Eurocode	Description	Length	Collation	Box Qty
011885	HC6 15 FH	15mm	White	500
053893	HC6 17 FH	17mm	White	500
053204	HC6 22 FH	22mm	White	500
053205	HC6 27 FH	27mm	White	500

10 strip collation (suitable for use in 20 and 40 pin magazine) + 1 x Fuel Cell.

HC6 Pins - Hard Concrete & Steel Substrates



HC6 collated pins for fixing into concrete and steel. Designed to increase success rate in substrates with higher aggregate content. Collation remains intact when fixed. Available in sizes from 15 - 32mm.

Eurocode	Description	Length	Collation	Box Qty
053206	HC6 15	15mm	Orange	500
011876	HC6 17	17mm	Orange	500
011891	HC6 22	22mm	Orange	500
011877	HC6 27	27mm	Orange	500
053207	HC6 32	32mm	Orange	500

10 strip collation (suitable for use in 20 and 40 pin magazine) + 1 x Fuel Cell

Pin Selection Guide:

	C6 SELECTION HC6									
	CLIP ELEC	CONDUIT CLIP	CT-CLIP	E-CAV	P-CLIP	CABLE BOW	STEEL BAND	METAL CLIPS	TRH CLIP**	FIREFIX™
STEEL	HC6 15-17	HC6 15-17		HC6 15-17		HC6 17-22		HC6 15		
HARD CONCRETE	HC6 17-22	HC6 22		HC6 17-22		HC6 22		HC6 15-17		
CONCRETE & BRICK	HC6 22-27	HC6 27		HC6 22-27		HC6 27-32		HC6 17-22		
	C6 25-30	C6 30		C6 25-30		C6 30-35		C6* 20-25		

* Site test recommended. Call the Technical Helpline on 0800 7314924.

** Threaded Rod maximum length 600mm and static loads only.