

## Cementitious Board Screws

### Application

Fixing cementitious boards and sheathing to track and timber.



Product Code	Description	Size	Box Quantity	Carton Quantity
<a href="#">WHL08158</a>	Cementitious Board Screw with Hi-Lo Thread and Spoon Point	4.2mm x 42mm	200	4,800
<a href="#">WHL08114</a>	Lo Thread and Spoon Point	4.2mm x 32mm	200	4,800
<a href="#">WHP08114</a>	Screw	4.2mm x 32mm	200	4,800
<a href="#">WHP08158</a>	Screw	4.2mm x 42mm	200	4,800

### Ruspert® Coating

Ruspert® is a non-organic, tri-layered ceramic surface coating developed to attain optimum performance in the various pollutant and atmospheric conditions that cause corrosion.

Layer 1: metallic zinc

Layer 2: high-grade anti-corrosion chemical conversion film

Layer 3: baked ceramic top coating

The distinguishing feature of Ruspert® is the tight joining of the baked ceramic top coating and the chemical conversion film thanks to the cross-linking effect. These layers are bonded together with the metallic zinc layer through chemical reactions, and this unique method of combining layers results in a rigid and dense combination of the coating films. Ruspert® treatment does not attribute its anti-corrosion properties to merely a single material, but the synergy of these three layers, which combined have superb rustproof qualities.

Compatible with metal coated and painted surfaces, fasteners coated with Ruspert® are resistant to acid and alkaline attack, galvanic corrosion and hydrogen embrittlement. These fasteners conform to corrosive gas test standard (Kesternich) DIN50018 and give a salt spray fog test to exceed (JISZ2731) 1,000 hours (ASTM B117).

Copyright © 2010 Evolution Fasteners (UK) Ltd. All rights reserved.

Drywall

## Tough Board Screws

### Application

Fixing dense and hard surfaced boards to both drywall track and timber base materials.

Fixing low/medium density boards to drywall track and timber.



Product Code	Description	Size	Box Quantity	Carton Quantity
<a href="#">F35</a>	Tough Board Screw	3.9mm x 35mm	1,000	10,000
<a href="#">F45</a>	Tough Board Screw	3.9mm x 45mm	1,000	10,000
<a href="#">DVRT32</a>	Reverse Thread Drywall Screw	3.9mm x 32mm	1,000	10,000
<a href="#">DVRT42</a>	Reverse Thread Drywall Screw	3.9mm x 42mm	1,000	10,000

### Application Information

Evolution tough board screws should be used instead of standard

drywall fixings for dense board types e.g. Fermacell, Knauf Toughpanel and British Gypsum Gyproc Duraline as standard fixings can either break or fail to countersink flush.

As a general guideline\*, dense board types should be fixed to the studs using Evolution tough board screws at 250mm centres along the studs.

i.e. for 500mm stud spacing you will need 26 screws per m<sup>2</sup>

for 600mm stud spacing you will need 24 screws per m<sup>2</sup>

\* Please note that this information is only provided as a general guideline because it is not possible to predict interal pressure forces.