

Triga Z High Performance Safety Anchor Bolt Version (V)

Code	Description	Thread Ø	Drill Ø	Max Fixture	Box Qty
50673	V6-10/5	M6	10mm	5mm	100
50674	V6-10/20	M6	10mm	20mm	100
50677	V8-12/1	M8	12mm	1mm	100
50678	V8-12/10	M8	12mm	10mm	50
50679	V8-12/20	M8	12mm	20mm	50
53001	V8-12/50	M8	12mm	50mm	50
50687	V10-15/1	M10	15mm	1mm	25
50688	V10-15/10	M10	15mm	10mm	25
50689	V10-15/20	M10	15mm	20mm	25
53003	V10-15/55	M10	15mm	55mm	25
50696	V12-18/10	M12	18mm	10mm	25
50697	V12-18/25	M12	18mm	25mm	25
53004	V12-18/55	M12	18mm	55mm	25
50704	V16-24/10	M16	24mm	10mm	10
50705	V16-24/25	M16	24mm	25mm	10
50710	V16-24/50	M16	24mm	50mm	10
50711	V20-28/25	M20	28mm	25mm	5

Triga Z Loose Nut Version (E)

Code	Description	Thread Ø	Drill Ø	Max Fixture	Box Qty
50675	E6-10/50	M6	10mm	50mm	100
50681	E8-12/20	M8	12mm	20mm	50
50683	E8-12/35	M8	12mm	35mm	50
50684	E8-12/55	M8	12mm	55mm	50
50685	E8-12/95	M8	12mm	95mm	25
50691	E10-15/20	M10	15mm	20mm	25
50692	E10-15/35	M10	15mm	35mm	25
50693	E10-15/55	M10	15mm	55mm	25
50694	E10-15/100	M10	15mm	100mm	25
50699	E12-18/10	M12	18mm	10mm	25
50698	E12-18/25	M12	18mm	25mm	25
50699	E12-18/45	M12	18mm	45mm	20
50701	E12-18/65	M12	18mm	65mm	10
50702	E12-18/100	M12	18mm	100mm	20
50706	E16-24/25	M16	18mm	25mm	10
50707	E16-24/55	M16	24mm	55mm	5
50708	E16-24/100	M16	24mm	100mm	5
50712	E20-28/25	M20	28mm	25mm	5
50713	E20-28/60	M20	28mm	60mm	5
50714	E20-28/100	M20	28mm	100mm	5

Triga Z Countersunk Version (TF)

Code	Description	Thread Ø	Drill Ø	Max Fixture	Box Qty
50686	V8-12/16	M8	12mm	16mm	50
53002	V8-12/26	M8	12mm	26mm	50
50695	V10-15/27	M10	15mm	27mm	25
50715	V12-18/40	M12	18mm	40mm	10

Triga Z Loose Nut Stainless Steel A4 Version (E)

Code	Description	Thread Ø	Drill Ø	Max Fixture	Box Qty
50598	E8-12/45	M8	12mm	45mm	50
50604	E10-15/45	M10	15mm	45mm	25
50606	E12-18/15	M12	18mm	15mm	25
50608	E12-18/45	M12	18mm	45mm	20
52940	E16-24/25	M16	24mm	25mm	10

Triga Z Loose Bolt Stainless Steel A4 Version (V)

Code	Description	Thread Ø	Drill Ø	Max Fixture	Box Qty
50594	V6-10/10	M6	10mm	10mm	100
50595	V8-12/10	M8	12mm	10mm	25
50596	V8-12/25	M8	12mm	25mm	25
50601	V10-15/25	M10	15mm	25mm	25
50605	V12-18/25	M12	18mm	25mm	25

Triga Z High Performance Safety Anchor



Product Advantages

- * Anti Rotational Z shape-creates sharp angled areas, ensuring the anchor is not rotated during tightening.
- * Markings-Sleeve marking indicates maximum thickness of the fixture to be fixed. The diameter thickness of the spacer is efficiently designed to enable heavy shear loads
- * Unique, all steel Zshape collapse system-Shearing action during tightening of the anchor ensures clamping pressure.Collapse cannot start before anchor has started to expand

- * Bolt and threaded rod- 8.8 grade steel for high performance



Substrates

- * Concrete
- * Solid stone

Applications

- *Channel Supports
- *Pipe Supports
- *Heating Pumps
- *Ventilation
- *Safety Barrier/ Balustrades
- *Shelving & Racking

