

Product datasheet

Stitching tek screw



| | |
|---------------------------------|----------------------------|
| Designed for: | Stitching cladding panels. |
| Head Style: | Hexagonal |
| Drive Bit: | 5/16" Hexagonal |
| Washer: | 16mm Ø bonded EPDM |
| Thread Form: | Twin |
| Coating: | 500hr silver Ruspert® |
| Shank Material: | Carbon Steel |
| Material Grade: | AISI C1022 |
| Recommended Drill Speed: | 2,000 - 3,000 RPM |
| Drilling Capacity: | 0.8mm - 2.5mm |



Stitching Tek Screw Range

| Product Code | Size | Box Qty | Carton Qty | Drill Point | Effective Thread Length | Steel Thickness |
|--------------|------------|---------|------------|-------------|-------------------------|-----------------|
| TST22G16 | 6.3 x 22mm | 100 | 8,000 | Tek 2 | 15mm | 0.5mm - 2.5mm |
| TMST25G16 | 8.0 x 25mm | 100 | 2,800 | Tek 1 | 18mm | 0.8mm - 2.5mm |

Product datasheet

Stainless steel

Stitching tek screws

| | |
|---------------------------------|--|
| Designed for: | Assembly/fabrication of heating, ducting and ventilation systems (SSH4.8-16-3) Fixing steel to steel (SSPH5.5-19-3) Stiching cladding panels (SSS6.3-22-2) |
| Washer on SSS6.3-22-2: | 16mm Ø bonded EPDM |
| Thread Form: | Twin |
| Shank Material: | Stainless steel |
| Material Grade: | AISI A410 |
| Recommended Drill Speed: | 1,500 - 2,500 RPM |

TST16SS



TST19SS



TST22SS16



Stainless Steel Stitching Tek Screw Range

| Product Code | Size | Box Qty | Carton Qty | Head Style | Drive Bit | Drill Point | Effective Thread Length | Drilling Capacity |
|--------------|------------|---------|------------|------------|-----------------|-------------|-------------------------|-------------------|
| TST16SS | 4.8 x 16mm | 1,000 | 10,000 | Hexagonal | 5/16" Hexagonal | Tek 3 | 10mm | 1.2 - 3.5mm |
| TST19SS | 5.5 x 19mm | 200 | 5,000 | Pancake | Phillips 3 | Tek 2 | 14mm | 1.2 - 3.5mm |
| TST22SS16 | 6.3 x 22mm | 100 | 8,000 | Hexagonal | 5/16" Hexagonal | Tek 2 | 15mm | 0.8 - 2.5mm |