Rytons Order/Specification Code	Main Uses, Features and Benefits	Size	Free Area	Colours	Approvals & Testing
Code: RYTWEEP	Rytons Rytweep® Unobtrusive cavity weep hole. Virtually unseen when installed; shows only small weep outlet. Lugs aid mortar adhesion. Quickly and easily fitted.	101mm L x 66mm H x 10mm W	Not applicable	B/S, TC, Clear, new GR	BBA BOTTEN GORPHICATE No. 89/2321 Irish Reg. Stat.
© Rytons				new colour	
Code: RYTWTUBE	Rytons Rytweep® Tube Extension for blockwork and rendered walls. Push fit into Rytons Rytweep®. Easily cut to length.	500mm L x 6mm Int. Dia. x 8mm Ext. Dia.	Not applicable	Clear	
Code: WEEPW-	Type W Weep Vent The type W is the first specifically conceived dual-purpose weep & vent. Aesthetically & practically designed with a functionally inclined front. The type W is finished with an insect resistant grill	105/115mm L x 65mm H x 10mm W	Not applicable	GR, BL, TC,WH,BS	BBA BRITISH AGREEME CERTIFICATE No. 89/23: Irish Reg. Stat.
Code: RTV250CL	Rytons Retro Weep Vent Retro-fit cavity ventilator and weep hole duct. Ideal solution when no provision has been made for cavity venting or weeps or an insufficient number have been installed. External fins provide a lock-tight fit. Flange covers drilling for a neat finish. Clear colour blends with any facing brick or render. Use in timber frame and traditional build.	80mm L (excl. flange) x 26mm Dia. (inc. fins)	250mm²	Clear	new
Code: SVFMIN	Rytons Flyscreened Slim Vent® Minor Flyscreened cavity ventilator. Use in timber frame and traditional build. An effective weep hole. Internal baffles prevent water transfer. No special fixing or brickwork required.  Rytons Slim Vents® are the ONLY timber frame vents	103mm L x 66mm H x 10mm W Allows 6mm venting gap	220mm²	GR, BL, B/S, TC, WH, Clear	BBA BRITISH FOR AGREEMEN CERTIFICATE No. 89/2321 Irish Reg. Stat.

## **Colour Key**

GR BL BS TC WH BR B/B Grey Black Buff/Sand Terracotta White Brown Blue/Black

## Multifix® Air Bricks and Periscope® Underfloor Ventilator

Rytons Order/Specification Code	Main Uses, Features and Benefits	Size	Free Area	Colours	Approvals & Testing
Code: SVMAJ	Rytons Slim Vent® Major Extra long cavity ventilator. Also cross-cavity and underfloor ventilator. Two sets of baffles prevent water transfer. No special fixing or brickwork required.	304mm L x 66mm H x 10mm W Allows 6mm venting gap	330mm²	Clear	BBA BRITISH GORAGO OF GORAGO
Code: MFAB96	Rytons '9x6' Multifix® Air Brick Robust interlocking '9x6' air brick. Textured finish maintains aesthetic appearance. Use with Rytons '9x6' Telescopic AirLiner® (TCL18000) and '9x6' Acoustic AirLiner® (TAL8000). U.V. stabilised to protect against fading by sunlight.	215mm L x 134mm H x 59mm D	15185mm² 151.85cm²	B/S, TC	BBA BIRTISH BBA BIRTISH GERTIN-CATE No. 94/2071 Irish Reg. Stat.
Code: MFAB	Rytons Multifix® Air Brick Robust interlocking air brick. One size can form a unit '9x6', '9x9' etc. Textured finish maintain aesthetic appearance. Use with Rytons Periscope® Underfloor Ventilator (PUFV) and AirLiners®' 9x3', '9x6' and '9x9'. U.V. stabilised to protect against fading by sunlight.	215mm L x 66mm H x 58mm D	7750mm² 77.5cm²	GR, BL, B/S, TC, WH, BR, B/B	BBA BRITISH GERTIFICATE No. 607/2021 Irish Reg. Stat.
Code: PUFV  Air brick sold separately  © Rytons	Rytons Periscope® Underfloor Ventilator For block and beam and timber floors. Alleviates build-up of dangerous gases. Expands up to 5 brick courses. Prevents damage by condensation. Use with Rytons Multifix® Air Brick (MFAB).	218mm W x 250mm D x 368mm H Fully extended with MFAB fitted	7750mm² with MFAB fitted	BL	BBA BRITISH BOARD OF LORIFICATE NO. 887-2821  Irish Reg. Stat.
Code: PUFVVEXT	Rytons Periscope® Vertical Extension  Vertical extension for Rytons Periscope® Underfloor  Ventilator (PUFV).  Easily installed with no extra fitting required.  May be cut to length.	1000mm L x 220mm W x 54mm D	Not applicable	BL	
Code: HADAP100	Rytons Horizontal Adaptor  Allows a connection from Rytons Non-Telescopic AirLiner® (TCL8LNR) to flexible or rigid ducting.  Allows a connection from Rytons Periscope®  Underfloor Ventilator (PUFV) to rigid ducting e.g. soil pipe for ventilation to isolated floor areas.	215mm L x 67mm H x 49mm D excl. tube connector x 101mm Dia. spigot	5980mm² 59.8cm²	BL	