

FlooringRange

A comprehensive range of high quality flooring products. Offering a variety of solvent-free self-levelling compounds, primers, surface DPM's and floorcovering adhesives.

Page Contents:

Primers & Membranes
Adhesives

Size: 10Kg

VD Primer

A universal, solvent-free primer for use on porous and non-porous substrates. Can be applied to both walls and floors in internal applications. Designed for use with "water based" levelling compounds and Schonox LC Latex if a primer is required. Quick drying times and good coverage rates (can be used neat or diluted depending on sub-floor). Carries EC1 rating for very low emissions.



PRODUCT CODE: **SCVD10**

Application: As a primer to reduce absorbency of substrates; as a primer to improve adhesion prior to levelling compound application; as a primer to protect against moisture from the levelling compound (see data sheet). Can be applied by brush, roller or spray. Suitable for use on most substrates and can be used over underfloor heating systems. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: 125 – 200m² per 10Kg unit.

Colours

Light Blue

Size: 5Kg

SHP Primer

A solvent-free, 1-part, acrylic dispersion primer. Can be applied to both walls and floors in internal applications. This primer contains special additives that make it suitable for use on dense impervious substrates. Ideal for priming over existing, firmly bonded, flexible floorcoverings prior to application of AP Gypsum levelling compound. This would include vinyl, linoleum and rubber coverings. It is recommended that this primer is only used where existing floorcoverings cannot be removed. Carries EC1 rating for very low emissions.



PRODUCT CODE: **SCSHP5**

Application: As an adhesion primer prior to levelling work. Suitable for terrazzo, ceramic tiles, natural stone, mastic asphalt, concrete, thermoplastic and semi-flexible tiles, lino, vinyl and rubber, metal (such as channelled plate), old coatings and sealers. Can be applied by brush, roller or application pad. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: Approx 40 -50m² per 5Kg unit.

Colours

Light Blue

Size: 10Kg

SDG Surface Membrane

A dispersion based, 1-part surface membrane. Two coat application, very quick drying & no primer required. Levelling compounds may be overlaid in 1-2 hours depending upon drying conditions.



PRODUCT CODE: **SCSDGPM**

Application: Currently for use at up to 90% RH. Carries EC1 rating for very low emissions. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: Approx 40 sq mtrs (2 coats) per 10Kg unit.


Colours

Gold

Size: 14Kg & 6Kg

Emiclassic

A truly multi-purpose, pressure sensitive, acrylic dispersion floorcovering adhesive. Suitable for probably 97% of all floorcoverings onto porous or non-porous sub-floors. Emiclassic will bond PVC, Designer PVC, Linoleum sheet, rubber up to 4mm thickness, cushioned vinyl, carpets and has recommendation by major floorcovering manufacturers. It is completely solvent-free and has low odour making it ideal for sensitive installations. It has a good bond strength, rapid curing properties, and requires only a short open time. Carries EC1 rating for very low emissions.



PRODUCT CODE: **SCEMI14** PRODUCT CODE: **SCEMI6**

Application: Emiclassic is a permanent bond adhesive. It is suitable for bonding textile wall and floor coverings, woven fabrics, needlepunch, PVC, vinyl, lino, cork and synthetic rubber coverings. This product in certain circumstances can be laid over old floorcoverings – please consult our technical department for further information. It is suitable for use with underfloor heating systems and has been tested for use with castor wheel loading according to DIN EN 12 529.

Approx coverage: 45 -70m² depending on type of floorcovering.

Colours

Beige

FlooringRange

Page Contents:

Self-levelling Compounds
Adhesives

Size: 25Kg

AP

A synthetic, gypsum, interior self-levelling compound. For use from 1mm – 30mm or 10mm -45mm when bulked out with silica sand / granite chippings. High strength values (40 Newton compression strength) with low stress. Protein-free, very low emissions (EC 1). It is suitable for use with underfloor heating systems and for castor wheel loading.

Application: May be used over all substrates but particularly over Gypsum screeds. It is used in conjunction with SHP primer to overlay old firmly bonded resilient floorcoverings. Product is pumpable. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: 25Kg of powder plus 6.0 litres water will cover approx 5.5m² @ 3mm thickness.

Colours

White



Size: 25Kg

APF

A synthetic, gypsum, fibre reinforced, interior self levelling compound. For use from 3-15mm thickness. This product has a high compression strength of 40 N/mm² but is also highly flexible and has low stress. It is protein-free, chromate free, has low pH values and good working properties. It carries the EC1 rating for very low emissions.

Application: Simply add water. Due to its high flexural strength this product is ideal for use on surfaces with movement capabilities, particularly on timber floor boards, chipboard (V100), plywood as well as most common substrates. It is also part of a system to renovate VERY bad subfloors of any construction. APF is quick drying and can take foot traffic in approximately 3 hours. It is pumpable & has a German patent. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: 25Kg of powder plus 5.5 litres water will cover approx 5.5m² @ 3mm thickness.

Colours

White

Size: 25Kg

FPL Plus

A cementitious, self-levelling, water mix, interior flooring compound. For use from 3mm – 40mm thickness or 10mm – 60mm when bulked out with silica sand / 3mm granite chippings. Has low stress levels, high strength values (25 Newton compression strength) and very low emissions (EC 1R). It is suitable for use with underfloor heating systems and for castor wheel loading. This product is protein-free and frost resistant.

Application: Simply add water as per bag instructions. Product is pumpable. Suitable for new build and refurb work and can be used over concrete, cement and gypsum screeds (refer to data sheet), new mastic asphalt screeds (IC10 & IC15). Both VD and SHP primers can be used with this product as required. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: 25Kg powder plus 4.4 litres water will cover approx 5m² @ 3mm thickness.


Colours

White

Size: 10L & 5L

Bond It LX16

A solvent based, heavy duty, interior adhesive for bonding all types of wood flooring. Ideal for use where the nature of the wood flooring makes it particularly prone to warping when bonded with a waterborne adhesive. Easy to spread with a high shear strength and short open time



PRODUCT CODE: **BDLX161** PRODUCT CODE: **BDLX162**

Application: Suitable for use on parquet flooring, woodblock and wood strip to most common substrates. Can be used with underfloor heating systems. Apply by triangular notched trowel, size as recommended by the wood flooring manufacturer. No waiting time necessary prior to laying wood flooring. Note: the correct sub-floor preparation must be conducted prior to laying any flooring systems. Consult our technical department for details.

Approx coverage: Notched Trowel TKB B3, B6, B10 approx. 1.33 – 1.5 m² per Kg, notched trowel TKB B11, B15 approx 0.83 – 1 m² per Kg.

Colours

Beige

Size: 15Kg

Bond It GP Adhesive

A solvent-free, high tack carpet adhesive with zero calculated VOC's and contains Microban anti-microbial protection.

Application: Will bond the majority of carpets including, backings of foam, actionbac, felt back, jute back, latex unitary back, needlepunch but NOT for use with PVC back carpet. It may also be used to bond both rigid and semi-flexible vinyl tiles but NOT fully flexible vinyls.



PRODUCT CODE: **BDGPA15** 15Kg

Approx coverage: 40 -45m² per 15Kg

Colours

Beige