

### Countersunk Tapcon Range

Code	Description	Thread Ø	Drill Ø	Fixture	Length	Box Qty
3F32	Csk Tapcon anchor	5mm	4mm	0-7mm	32mm	100
3F45	Csk Tapcon anchor	5mm	4mm	5-20mm	45mm	100
3F57	Csk Tapcon anchor	5mm	4mm	17-32mm	57mm	100
3F70	Csk Tapcon anchor	5mm	4mm	30-45mm	70mm	100
3F82	Csk Tapcon anchor	5mm	4mm	42-57mm	82mm	100
3F100	Csk Tapcon anchor	5mm	4mm	60-75mm	100mm	100
4F32	Csk Tapcon anchor	6mm	5mm	0-7mm	32mm	100
4F45	Csk Tapcon anchor	6mm	5mm	5-20mm	45mm	100
4F57	Csk Tapcon anchor	6mm	5mm	17-32mm	57mm	100
4F70	Csk Tapcon anchor	6mm	5mm	30-45mm	70mm	100
4F82	Csk Tapcon anchor	6mm	5mm	42-57mm	82mm	100
4F100	Csk Tapcon anchor	6mm	5mm	60-75mm	100mm	100
4F125	Csk Tapcon anchor	6mm	5mm	85-100mm	125mm	100



### Hex Head Tapcon

Code	Thread Ø	Drill Ø	Fixture	Length	Box Qty
3H32	5mm	4mm	0-7mm	32mm	100
3H45	5mm	4mm	5-20mm	45mm	100
3H57	5mm	4mm	17-32mm	57mm	100
4H32	6mm	5mm	0-7mm	32mm	100
4H45	6mm	5mm	5-20mm	45mm	100
4H57	6mm	5mm	17-32mm	57mm	100
4H70	6mm	5mm	30-45mm	70mm	100
4H82	6mm	5mm	42-57mm	82mm	100
4H100	6mm	5mm	60-75mm	100mm	100



NB. Supplied with one D end rotary percussion masonry bit in every box



### Applications

Saddles, conduit clips, back boxes, P Clips, cable clips, cable Cleats  
 Services  
 Ductwork, cable trays, channel, suspended ceilings, timber to concrete, formwork, battens, base plates, plywood backer boards insulation systems to masonry  
 Metalwork  
 Railings, hand rails, gates, brackets and signs, fire protection and exterior

### Product Features

Fast installation, Drill, Drive, Done  
 Available in M5 and M6 and in lengths from 32 - 125mm, to cover a wide number of applications  
 Every box includes a free 'close tolerance' masonry bit  
 Replaces small diameter expansion anchors, plugs and screws in light to medium duty applications  
 No need to pre-spot holes, no inserts are required  
 Removable - adjustable  
 Can be installed close to edges  
 Slotted Hex and Phillips flat head styles give flexibility in applications  
 Excellent corrosion protection  
 Fire resistant



SBCCI Approved 9759

Metro-Dade Approved 02 - 0311 - 03

ICBO Approved 3370

