

Description

Metal frame fixing  
By tightening the screw, the cone is drawn into the sleeve and the fixing is expanded which wedges it inside the drill hole.

code	descriptionm	drill	length	drill depth	effect		box
					anch dept	max usable	
F8M72	All metal Frame fixings	8mm	72mm	90mm	30mm	42mm	100
F8M92		8mm	92mm	110mm	30mm	62mm	100
F8M112		8mm	112mm	130mm	30mm	82mm	100
F8M132		8mm	132mm	150mm	30mm	102mm	100
F10M72		10mm	72mm	90mm	30mm	42mm	100
F10M92		10mm	92mm	110mm	30mm	62mm	100
F10M112		10mm	112mm	130mm	30mm	82mm	100
F10M132		10mm	132mm	150mm	30mm	102mm	100
F10M152		10mm	152mm	170mm	30mm	122mm	100
F10M182		10mm	182mm	200mm	30mm	152mm	100
F10M202		10mm	202mm	220mm	30mm	172mm	100



Advantages/benefits

The principle of installation prevents window frames from being pulled against the substrate.  
Locking lugs on the edge of the fixing provide strong joint resistance to both compressive and tensile loads; particularly with metal and plastic hollow sections.  
Aluminium-zinc-plated fixing sleeve ensures good corrosion protection.  
Cover caps to conceal fixing.

code	description	drill	length	drill depth	anch dept	max usable	
F8S100	All nylon Frame fixing	8mm	100mm	115mm	40mm	50mm	100
F8S120	All nylon Frame fixing	8mm	120mm	135mm	40mm	70mm	100
F8S140	All nylon Frame fixing	8mm	140mm	155mm	40mm	90mm	100
F10S75	All nylon Frame fixing	10mm	75mm	90mm	40mm	15mm	100
F10S100	All nylon Frame fixing	10mm	100mm	115mm	40mm	40mm	100
F10S120	All nylon Frame fixing	10mm	120mm	135mm	40mm	60mm	100
F10S140	All nylon Frame fixing	10mm	140mm	155mm	40mm	80mm	100
F10S165	All nylon Frame fixing	10mm	165mm	180mm	40mm	105mm	100



ADJUSTABLE PLUG FIXINGS

		drill	length	drill depth	anch dept	max usable
S10I75S	adjustable frame fixing complete	10mm	75mm	115mm	50mm	100



UNIVERSAL ADJUSTABLE SCREWS ASL

code	description	drill	length	drill depth	drive	max usable
ASL4.5X60	Universal adjustable standoff screws	6mm	60mm	40mm	t25	25mm
ASL4.5X70	Universal adjustable standoff screws	6mm	70mm	40mm	t26	35mm
ASL4.5X80	Universal adjustable standoff screws	6mm	80mm	40mm	t27	45mm
ASL4.5X90	Universal adjustable standoff screws	6mm	90mm	40mm	t28	55mm
ASL4.5X100	Universal adjustable standoff screws	6mm	100mm	40mm	t29	65mm
ASL4.5X120	Universal adjustable standoff screws	6mm	120mm	40mm	t30	85mm
ASL6X80	Universal adjustable standoff screws	8mm	80mm	55mm	t31	35mm
ASL6X100	Universal adjustable standoff screws	8mm	100mm	55mm	t32	55mm
ASL6X120	Universal adjustable standoff screws	8mm	120mm	55mm	t33	75mm
ASL6X150	Universal adjustable standoff screws	8mm	150mm	55mm	t34	105mm
ASL6X180	Universal adjustable standoff screws	8mm	180mm	55mm	t35	135mm
ASL6X200	Universal adjustable standoff screws	8mm	200mm	55mm	t36	155mm

Description

JUSS STAND OFF SCREWS

code	description	drill	min-hole	anc/depth	max timb	max adj
J56X110	Adjustable Stand off screws	5mm	50-110mm	30mm	25mm	55mm

JUSS self-drilling adjustable screw with TX star recess-drive.  
Turning the screw anti-clockwise adjusts the distance of the wooden batten from the wall.

Advantages/benefits

Quick infinitely variable adjustment of wooden substructures in stand-off installations.  
Stress-free installation without blocks or wedges.  
Easy glide coating on the screw provides a low screw-in torque.  
No preliminary drilling is necessary with type JUSS.

